

# Rollei RETRO 100 Rollei RETRO 400

Fast, fine grain, ideal for general purpose and fine art photography

The ROLLEI RETRO 100 is a panchromatic sensitised Black & White film with a medium speed of ISO 100/21°. The film can be applicated for any general purpose and is suitable for almost every professional tasks. Owing fine grainess, the exposure range of practically one f=stop over- and underexposure capacity, photo prints can be achieved, with an excellent sharpness and contrast, as well as high edge sharpness.

The ROLLEI RETRO 400 is a panchromatic sensitised Black & White film material with a high speed of ISO 400/27°. The film is enormously efficient and reliable, also within bad lighting conditions. A further vital point: Actually designed for high sensitivity, the film can be pushed also up to ISO 800/30° with special processing.

Best contrasts in reference to finest grain and special tonal range can be reached by over-exposing the film material by approximately one f=stop, by processing the film in ROLLEI LOW SPEED developer (at ISO 50 with the RETRO 100 and/or ISO 200 with the RETRO 400).

- pancromatic medium and high speed b&w films;
- special coating for an improvement of the transport properties of the cameras;
- suitable for daylight and tungsten:
- spectral sensitization 380 630nm;

35mm = 120µm, rollfilm = 95µm, cellulose triacetate Film base:


Layer

- emulsion side: emulsion coating, antihalation coating


- back: NC "non-curling" coating RETRO  $100 - 7\mu m$ Layer thickness: RETRO 400 - 10µm

RETRO 100 - 150 lines/mm Resolving power: RETRO 400 - 110 lines/mm ISO 100/21° and ISO 400/27° **Exposure index:** 

# Charakteristische Kurven



Spektrale Empfindlichkeit Retro 400 lg Sensitivity



Developer

### Storage:

It is recommend not to leave the film material exposed into direct sunlight, strong heat or relative high humidity.

- unexposed film: Up to 24 months in cold storage by 8° C is recommend
- After exposure, please keep film in cold condition, processing as soon as possible is recommend - exposed film:

## **Processing:**

The ROLLEI RETRO 100 and 400 must be processed in complete darkness. It can be developed succesfully in all standard, developers such as AGFA, ILFORD, KODAK, LABOR PARTNER or TETENAL. To achieve optimal results, a test development is recommended in order to obtain the correct development times and temperatures. By using other developers - not tested by MACO - decreases of quality can be expected showing rough grain structures and low sensitivity.

### Highly recommended are the following developers:

Application

ROLLEI RHS **HIGH SPEED** Pictorial use, standard Pictorial use, extremly fine grain unsurpassed tonal range **ROLLEI RLS** LOW SPEED

The development time chart can be found in the internet under www.rollei.com.

Packing:

35mm 135 - 36 prof. pack of 10 Artikel No.: RR1011P/40111P Artikel No.: RR1030/4030 35mm - 30.5mRollfilm 120 TRIPLEX prof. Pack of 12 Artikel No.: RR1001P/4001P LOW SPEED Artikel No.: RLS11 ROLLEI photo chemistry HIGH SPEED 1 + 7Artikel No.: RHS11 HIGH CONTRAST 1+4 Artikel No.: RHC11 SHORT STOP 1 + 16Artikel No.: RSS11 Artikel No.: RFX11 **FIXIFRER** 1 + 7 - 1 + 9WETTING AGENT 1 + 1.000 Artikel No.: RWA12

Titel picture / Copyright by: Jens Kollmorgen, Germany